



**MIDCOM Data
Technologies®**, Inc.
"Your Business. The Right Solution."

Call Today!
(800) 643-2664

CLI LT4100 Teradici Zero Client

Everything you need in a slim form

Using PC-over-IP technology the LT4100 is based on the next generation Tera2 PCoIP processor from Teradici. With host-based pixel encoding, this client optimizes network bandwidth while delivering an unparalleled user experience. The LT4100 is a perfect fit for any organization that is looking for a secure, low maintenance thin client that will deliver an amazing end user experience. Capable of handling even the most graphics intensive applications, this client really delivers for your IT staff and end users.

Zero client for VMware environments

A true fit for Virtual Desktop environments, CLI's LT4100 includes enhanced security, featuring zero client architecture without exposed API's or application ports. This secure, zero client requires minimal management and maintenance. The LT4100 also delivers a superior end-user experience over 2 HD displays with high resolution and full frame rate 3D graphics. The best of both worlds, with a rich multimedia offering and easy manageability, make CLI's LT4100 the right VDI end-point solution for any organization.

At a Glance

Secure, zero client designed for VMware environments. It supports dual DVI displays and is ready to plug and play with easy implementation and effortless management. Provides an excellent user experience.

Features

- No moving parts provides the highest reliability
- Dual DVI with resolution up to 2560 x1600 pixels
- Four USB 2.0 ports
- 512 MB DDR3 RAM
- Low power consumption at under 8 Watts
- Full power management with Wake-on-LAN support
- PCoIP and RDS over PCoIP virtual desktops or remote workstation hosts using VMware View Client



CLI LT4100 Teradici Zero Client

Modular logic unit, Tera 2321 PCoIP, Gigabit Ethernet, onboard DRAM, 4 USB 2.0 ports, audio in/out ports, external power supply, security lock slot, mouse, keyboard, three-year warranty.

CONFIGURATION	DESCRIPTION
Operating system	No Local OS
VESA mount	Optional accessory
Processor	Teradici Tera 2321 PCoIP® Processor
Chipset	TERA2
Video	Up to 1920x1200 when using dual displays. Single display up to 2560 x 1600 resolution (1) DVI-D (1) DVI-I, (1) DVI-VGA adapter is included in the box
Memory	Onboard 32-bit DDR3-1066 512MB SDRAM
Flash	Zero
Ruggedized Slim Design	Equipped with an industrial strength rugged metal case and plastic cover
Communications	(1) Gigabit Ethernet port (fiber optional)
Ports and Connectors	(4) USB 2.0 ports (2 front, 2 rear), (1) DVI-D and (1) DVI-I, (1) Gigabit Ethernet, (1) mic-in jack, (2) audio out jacks
Wireless	Not Available
Security	Kensington lock slot
Operating temperature	32 °F to 104 °F 20% to 80% non-condensing humidity
Protocol	PCoIP, RDS over PCoIP using* VMware View Client
Full Weight	1.7 lbs
Dimensions	(W x D x H) 4.2 x 14 x 19.8 cm (W x D x H) 1.7 x 5.5 x 7.8 inches

*Requires Teradici Arch server, and other components on the 2008 WTS server backend