



**MIDCOM Data
Technologies®**, Inc.
"Your Business. The Right Solution."

Call Today!
(800) 643-2664

Printronix 6600 Series of Line Matrix Printers

the Power
of



Technical Specifications

Printer Features	Open 6605 Pedestal 6610 6615	Quiet 6605 Pedestal 6610 6615	Zero Tear 6605Z 6610Z 6615Z	Cabinet 6605Q 6620Q 6610Q 6615Q	
Standard					
Integrated Print Management	•	•	•	•	
Ribbon Life Monitor	•	•	•	•	
Options					
SureStak® Power Stacker				•	
Black back forms paper out sensor	•	•	•	•	
Rear Slide Out Paper Drawer				•	
Cabinet Front Access				•	
Pedestal Front Paper Tray	•		•		
Pedestal High Rear Paper Tray	•	•	•		
Pedestal Acoustic Shroud	•	Standard			
Physical Size	Height	36"(914.4mm)	36"(914.4mm)	42"(1066.8mm)	40.5"(128.7mm) 40.5"(1028.7mm)
	Width	26"(660.4mm)	26"(660.4mm)	26"(660.4mm)	27"(685.8mm) 27"(685.8mm)
	Depth	21.5"(546.1mm)	25"(635mm)	21.5"(546.1mm)	29"(736.6mm) 33"(838mm)
	Shipping Weight	165 lbs (74.842kg) Not including rear tray	190 lbs (86.182kg) With acoustic shroud	180 lbs (81.646kg)	265 lbs (120.201kg) 300 lbs (136kg) With SureStak Power Stacker
Acoustic (dBA) (per ISO 7779)	6605- 62	6605- 58	6605Z- 66	6605Q- 50	
	6610- 65	6610- 60	6610Z- 70	6610Q- 50	
	6615- 68	6615- 63	6615Z- 70	6615Q- 52 6620Q- 55	
	6605 6605Q 6605Z	6610 6610Q 6610Z	6615 6615Q 6615Z	6620Q	
Print Speed (LPM, upper case characters, lower case characters)	High Speed (draft)	500/428	1000/856	1500/1289	2000/1700
	Data Processing	375/300	750/600	1125/900	1500/1200
	Near Letter Quality	200/154	400/306	600/459	800/615
Graphics Speed (Inches Per Minute)	60 x 48 dpi	63	125	187	250
	60 x 72 dpi	42	83	127	167
	90 x 96 dpi	21	42	61	83
Paper Feed Speed (Inches Per Second)	12	20	25	38.5	



Printronix 6600 Family of Line Matrix Printers

Character Pitch	5, 6, 6.7, 7.5, 8.3, 8.6, 10, 12, 13.3, 15, 16.7, 17.1, 20 (characters per inch)		
Line Spacing	1.5, 2, 3, 4, 5, 6, 8, 9, 10, 12 (lines per inch – plus variable line spacing)		
Graphics Resolution	240 dpi Horizontal, 288 dpi Vertical (max)		
Dot Size	16.7 mil (.42mm)		
Emulations Standard	Tally ANSI, Genicom ANSI, P5000/P600/P6000, Epson FX-1180, IBM Proprinter, MTPL (Tally Dot Matrix), PGL (TG Version), QMS Code V, Tally Industrial Graphics, PCL-3: HP-2564C, DEC LG01		
Character Sets	47 languages and 43 character sets		
Character Styles	Bold, italic, superscript, subscript, underline, overline, strike-through		
Fonts	Draft, Data Processing, Courier, Gothic, OCR A and B		
Barcodes	Code 39, Code 128, Interleaved 2 of 5, UPC-A, UPC-E, EAN 8, EAN 13, EAN 128, Codabar, MSI, PDF-417, Postnet, Intelligent Mail Barcode (IMB)		
Printer Software	TallyGenicom PrintNet Suite of Tools - remote management software suite - included with the Ethernet option		
Printer Drivers	Win 7, Vista, XP, Windows 2000, Server 2003, Server 2008, Server 2008r2, Linux, Unix, AIX, SAP		
Environmental Advantages	ENERGY STAR® qualified, lower consumable materials and packaging, improved handling of recycled paper, faster power-up from sleep mode than laser printers		
Genuine TallyGenicom Cartridge Ribbons	Standard Life	17,000 pages	
	Extended Life*	30,000 pages	*Not compatible with 500 LPM printer models
Paper Path/Handling	Straight paper path with easy-load adjustable tractors, paper-out detection and alarm, paper-motion detection and alarm		
Paper Type	Continuous, fan folded, edge-perforation		
Print Width	13.6" (345mm)		
Media Width	3" (76mm) to 17" (432mm)		
Media Copies	Up to 6 parts		
Media Weight	15 to 100 lbs up to 0.025" thickness 56 to 163 gm/m ² up to 0.64mm thickness		
MTBF*	10,000 hours at 25% duty cycle and 25% page density(*Mean Time Between Failures)		
Interfaces	Serial – RS-232 Parallel – IEEE-1284/Centronics Ethernet – PrintNet Suite 10/100 Base T (optional) Auto Switching – Between active ports		
Power Voltage	AC input range 88-270 VAC, 45 to 65 HZ		
Power Wattage (ENERGY STAR)	Less than 14 Watts in energy saving mode		
Power Wattage (typical)	6605/6605Q/6605Z	175 Watts	6615/6615Q/6615Z 390 Watts 6610/6610Q/6610Z 260 Watts 6620Q 475 Watts



MIDCOM Data Technologies®, Inc.

(800) 643-2664 | www.midcomdata.com

© 2011 Printronix, Inc. All rights reserved. Genicom, Tally, TallyGenicom, TG TallyGenicom, the TG Logo, Intellifilter, Intelliprint, PrintNet Suite, PrintNet Enterprise, PrintNet, Smart Ribbon and Printronix are trademarks or registered trademarks of Printronix, Inc. All other trademarks, product names, company names or logos herein are the property of their respective owners. Product appearance and/or specifications are subject to change without notice. Printed in USA. PTX_602A(4/11)